

Mirror- Wall Mount

JCP Models

	<u>Description</u>
J-1-0501	Large Mirror (as shown)
J-1-0502	Large Mirror w/ Back Plate
J-1-0503	Large Mirror w/ Embed
J-1-0504	Small Mirror
J-1-0505	Small Mirror w/ Back Plate
J-1-0506	Small Mirror w/ Embed



JCP Specifications: The overall size of the large mirror assembly is 12-3/8" x 16-3/8" x 5/16" thick, with the actual mirror area of 10" x 14". The mirror panel is 20 gauge stainless steel polished to a mirror finish approximating that of glass. The mirror frame is 14 gauge steel with a satin chrome finish.

The mirror, frame, and screws are shipped separate for field assembly and installation.

The assembly of the mirror and frame in the field is with 1/4-20 flat head Torx security screws that are included. A security screw driver bit is required but is not included. The wall must be flat and plumb with tapped holes for the mounting screws. It is recommended that security caulking be applied around the mirror frame to prevent objects from being inserted between the wall and the mirror frame. Security caulk is not included.

An optional back plate is 12-3/8" x 16-3/8" x 7 gauge HRPO steel, primed painted, with pre tapped holes for the mirror assembly and three 7/16" dia. holes countersunk for flathead expansion anchors to mount the back plate to the wall. The expansion anchors are provided by the installer. The back plate is shipped separate and must be installed flat and plumb against the wall that is fully grouted.

An optional embed is the above referenced 12-3/8" x 16-3/8" x 7 gauge HRPO steel back plate, primed painted, with three 12 gauge HRPO steel x 4" anchor straps for embedding into the wall. The back plate is shipped separate and must be installed by the mason flat and plumb against the wall with a #4 rebar (provided by others) inserted through each anchor, and then the wall must be fully grouted. Clean any grout or other material out of the mirrors mounting holes. Walls must be flat and true within 1/16" +/- for the proper installation of the mirror.

The overall size of the small mirror assembly is 10" x 11-1/2" x 5/16" thick, with the actual mirror area of 8" x 9-1/2". The mirror panel is 20 gauge stainless steel polished to a mirror finish approximating that of glass. The mirror frame is 14 gauge steel with a satin chrome finish. The optional small mirror back plate and embed are as described above, sized to the small mirror dimensions.

JAILS CORRECTIONAL PRODUCTS A Division of **FABCOR, Inc.**

350 South Ohio Street, P.O. Box 58
Minster, Ohio 45865
www.fabcor.com

Phone: (419) 628- 4428
Fax: (419) 628- 2899
E-mail: jails@fabcor.com

Equipment Assembly

EA-01.01

Revision C

©2003 Fabcor, Inc.